

VDS	RDS(on)	ID@25℃
1200V	40mΩ	68A

Applications:

- Solar Inverters
- Switch Mode Power Supplies
- High Voltage DC/DC Converters
- EV Charging
- Motor Drives

Features:

- High Blocking Voltage with Low On-Resistance
- High Speed Switching with Low Capacitances
- Easy to Parallel and Simple to Drive
- Avalanche Ruggedness

Benefits:


- Higher System Efficiency
- Reduced Cooling Requirements
- Increased Power Density
- Increased System Switching Frequency

Ordering Information

Part Number	Package	Marking	Packing	Qty.	
RSM120040Z	TO-247-4	RSM120040Z	Tube	30 PCS	

Maximum Ratings (TJ= 25°C unless otherwise specified)

Symbol	Parameter	Value	Unit	Test Conditions	Note
VDSmax	Drain - Source Voltage	1200	V	VGS=0V,ID =100µA	
VGSmax	Gate - Source Voltage	-8/+22	V	Absolute maximum values	
VGSop	Gate - Source Voltage	-4/+18	V	Recommended operational values	
ID	Continuous Drain Current	68 49	А	VGS=18V, TC =25℃ VGS=18V, TC =100℃	
ID(pulse)	Pulsed Drain Current	100	А	Pulse width tp limited by TJmax	
PD	Power Dissipation	340	W	TC =25℃, TJ =175℃	
TL	Solder Temperature	260	°C		
TJ, Tstg	Operating Junction and StorageTemperature	-55 to + 175	°C		





Electrical Characteristics (TJ= 25° C unless otherwise specified)

Symbol	Parameter	Min.	Тур.	Max.	Unit	Test Conditions	Note
V(BR)D SS	Drain-Source Breakdown Voltage	120 0			V	VGS=0V,ID =100μA	
	Gate Threshold	1.9	2.6	4.0	V	VGS= VDS, IDS=9.5mA,TC =25℃	
VGS(th)	Voltage		1.8		V	VGS= VDS, IDS=9.5mA,TC =175℃	
IDSS	Zero Gate Voltage Drain Current		1	100	μA	VDS= 1200V, VGS=0V	
IGSS	Gate-Source Leakage Current		10	250	nA	VGS=22V, VDS= 0V	
	Drain-Source on-state		40	53	mΩ	VGS=18V, ID =33.3A, TC =25℃	
RDS(on)	Resistance	6				VGS=18V, ID =33.3A, TC =175℃	
Ciss	Input Capacitance		207 0				
Coss	Output Capacitance		112		pF	VGS=0V, VDS=1000 V, f=1MHz, VAC=25 mV	
Crss	Reverse Transfer Capacitance		11				
EON	Turn-On Switching Energy		141 0		μJ	VDS =800V, VGS =-4/18V,ID = 33.3A,	
EOFF	Turn-Off Energy		750		μ	RG(ext) = 2.5Ω, L= 200μH	
td(on)	Turn-On Delay Time		17				
tr	Rise Time		58		nc	VDS =800V, VGS =-4/18 V	
td(off)	Turn-Off Delay Time		26		ns	ID = 33.3A, RG(ext) =2. 5 Ω , RL =20Ω	
tf	Fall Time		15				
RG(int)	Internal Gate Resistance		4.9		Ω	f=1 MHz, VAC=25mV	
Qgs	Gate to Source Charge		34		nC		
Qgd	Gate to Drain Charge		20		nC	VDS=800V, VGS=-4/18V ID =33.3A	
Qg	Total Gate Charge		121				



Reverse Diode Characteristics (TJ= 25° C unless otherwise specified)


Symbol	Parameter	Тур.	Max	Unit	Test Conditions	Note
		4.5		V	VGS=-4V, ISD = 20 A, TJ = 25℃	
VSD	Diode Forward Voltage	4.2		V	VGS=-4V, ISD= 20 A, TJ= 175℃	
IS	Continuous Diode Forward Current		51	A	VGS=-4V,TC= 25 ℃	
trr	Reverse Recovery time	38		ns		
Qrr	Reverse Recovery Charge	109		nC	ISD= 33.3 A, VR = 800V	
Irrm	Peak Reverse Recovery Current	5		A		

Thermal Characteristics (TJ= 25°C unless otherwise specified)

Symbol	Parameter		Unit	Test Conditions	Not e
RθJC	Thermal Resistance from Junction to Case	0.44	°C /\A/		
RθJA	Thermal Resistance From Junction to Ambient	40	°C/W		



Typical Feature Curve



REV:W-B01-03-2024 www.reasunos.com






Figure 11. Threshold Voltage vs. Temperature








Figure 13. 3rd Quadrant Characteristic at 25C







Figure 15. Capacitances vs. Drain-Source Voltage (0 - 200V)















Package outline drawing(TO-247-4 Unit: mm)







RECOMMENDED LAND PATTERN



UNIT: mm

	MIN	NOM	MAX
А	4.80	5.00	5.20
A1	2.25	2.40	2.45
A2	1.85	2.00	2.15
b	1.05	1.20	1.35
b1	1.00	1.30	1.60
b2	2.35	2.65	2.95
с	0.50	0.60	0.70
D	22.34	22.54	22.74
D1	16.00	16.50	17.00
D2	0.97	1.17	1.37
е	2.34	2.54	2.74
e1	4.88	5.08	5.28
Е	15.60	15.80	16.00
E1	13.50	14.00	14.50
E2	4.80	5.00	5.20
L	18.08	18.38	18.68
L1	2.38	2.58	2.78
р	3.50	3.60	3.70
p1	6.60	6.80	7.00
Q	6.00	6.15	6.30
S	6.00	6.15	6.30



Disclaimers:

Reasunos Semiconductor Technology Co.Ltd (Reasunos) reserves the right to make changes without notice in order to improve reliability,function or design and to discontinue any product or service without notice .Customers should obtain the latest relevant information before orders and should verify that such information in current and complete.All products are sold subject to Reasunos's terms and conditions supplied at the time of orderacknowledgement.

Reasunos Semiconductor Technology Co.Ltd warrants performance of its hardware products to the speciffications at the time of sale.Testing,reliability and quality control are used to the extene Reasunos deems necessary to support this warrantee. Except where agreed upon by contr- actual agreement,testing of all parameters of each product is not necessarily performed.

Reasunos Semiconductor Technology Co.Ltd does not assume any liability arising from the use of any product or circuit designs described herein.Customers are responsible for their products and applications using Reasunos's components.To minimize risk,customers must provide adequate design and operating safeguards.

Reasunos Semiconductor Technology Co.Ltd does not warrant or convey any license eith- er expressed or implied under its patent rights, nor the rights of others. Reproduction of inform- ation in Reasunos's data sheeets or data books is permissible only if reproduction is without modification oralteration. Reproduction of this information with any alteration is an unfair and deceptive business practice. Reasunos Semiconductor Technology Co.Ltd is not responsi- ble or liable for such altered documentation.

Resale of Reasunos's products with statements different from or beyond the parameters stated by Reasunos Semiconductor Technology Co.Ltd for that product or service voids all exp- ress or implied warrantees for the associated Reasunos's product or service and is unfair and deceptive business practice. Reasunos Semiconductor Technology Co.Ltd is not responsi- ble or liable for such statements.

Life Support Policy:

Reasunos Semiconductor Technology Co.Ltd's Products are not authorized for use as cri- tical components in life support devices or systems without the expressed written approval of Reasunos Semiconductor Technology Co.Ltd.

As used herein:

1. Life support devices or systems are devices or systems which: a.are intended for surgical implant into the human body, b.support or sustain life,

c.whose failuer to when properly used in accordance with instructions for used provided in the laeling,can be reasonably expected to result in significant injury to the user.

2.A critical component is any component of a life support device or system whose failure to system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.