


ID	R _{Ds(ON)} (Typ)	VDSS
30A	25mΩ	60V


Applications:

- Load Switch
- PWM Applications
- Power Managment

Features:

- Super Low Gate Charge
- Green Device Available
- Excellent CdV/dt effect decline
- Advanced Trench technology

Ordering Information

Part Number	Package	Marking	Packing	Qty.
RS60N30D	T0-252	RS60N30D	Tape&reel	2500 PCS

Absolute Maximun Ratings Tc= 25°C unless otherwise specified

Symbol	Parameter	RS60N30D	Units
VDSS	Drain-to-Source Voltage	60	V
ID	Continuous Drain Current TC=25°C (Note 1)	30	A
ID	Continuous Drain Current TC=100°C (Note 1)	18	
IDM	Pulsed Drain Current (Note 2)	120	
PD	Power Dissipation TC=25°C (Note 3)	44	W
VGS	Gate- to- Source Voltage	±20	V
EAS	Single Pulse Avalanche Engergy L = 0.5mH, VDD =36V, VGS=10V,IAS=13A	42.3	mJ
TL TPKG	Maximum Temperature for Soldering	300 260	°C
	Leads at 0.063in(1.6mm)from Case for 10 seconds		
	Package Body for 10 seconds		
TJ and TSTG	Operating Junction and Storage Temperature Range	-55 to 150	

* Drain Current Limited by Maximum Junction Temperature

Caution: Stresses greater than those listed in the“ Absolute Maximum Ratings” Table may cause permanent damage to the device.

Thermal Resistance

Symbol	Parameter	RS60N30D	Units	Test Conditions
R θ JC	Junction-to-Case (Note 1)	3.4	$^{\circ}\text{C} / \text{W}$	Drain lead soldered to water cooled heatsink, PD adjusted for a peak junction temperature of + 1 5 0 $^{\circ}\text{C}$

OFF Characteristics T_J= 25 $^{\circ}\text{C}$ unless otherwise specified

Symbol	Parameter	Min.	Typ.	Max.	Units	Test Conditions
BVDSS	Drain- to- source Breakdown Voltage	60	--	--	V	VGS=0V ID=250 μA
IDSS	Drain- to- Source Leakage Current	--	--	1	μA	VDS=60V VGS=0V
IGSS	Gate- to- Source Forward Leakage	--	--	100	nA	VGS=20V VDS=0V
	Gate- to- Source Reverse Leakage	--	--	-100		VGS=-20V VDS=0V

ON Characteristics T_J=25 $^{\circ}\text{C}$ unless otherwise specified

Symbol	Parameter	Min.	Typ.	Max.	Units	Test Conditions
RDS(on)	Static Drain- to- Source On-Resistance (Note 2)	--	25	30	m Ω	VGS=10V ID=15A
		--	32	40	m Ω	VGS=4.5V ID=10A
VGS (TH)	Gate Threshold Voltage	1.0	1.5	2.5	V	VGS=VDS ID=250 μA

Resistive Switching Characteristics Essentially independent of operating temperature

Symbol	Parameter	Min.	Typ.	Max.	Units	Test Conditions
td(ON)	Turn- on Delay Time	--	7.8	--	nS	VDS=30V VGS=10V ID=10A RG=2 Ω
trise	Rise Time	--	20	--		
td(OFF)	Turn- OFF Delay Time	--	15.6	--		
tfall	Fall Time	--	23	--		

Dynamic Characteristics Essentially independent of operating temperature

Symbol	Parameter	Min.	Typ.	Max.	Units	Test Conditions
Ciss	Input Capacitance	--	836	--	pF	VGS=0V VDS=30V f=1.0MHz
Coss	Output Capacitance	--	61	--		
Crss	Reverse Transfer Capacitance	--	50	--		
RG	Gate Resistance	--	1.2	--	Ω	VGS=0V VDS=0V f=1.0MHz
Qg	Total Gate Charge	--	20.6	--	nC	VDS=30V ID=10A VGS=10V
Qgs	Gate- to- Source Charge	--	2.5	--		
Qgd	Gate-to-Drain(" Miller") Charge	--	6	--		


Source- Drain Diode Characteristics

Symbol	Parameter	Min.	Typ.	Max.	Units	Test Conditions
IS	Continuous Source Current	--	--	30	A	Integral pn- diode in MOSFET
ISM	Maximum Pulsed Current	--	--	120	A	
VSD	Diode Forward Voltage	--	--	1.2	V	IS=10A VGS=0V
trr	Reverse Recovery Time	--	30	--	nS	VGS=0V IS=10A di/dt=100A/μs
Qrr	Reverse Recovery Charge	--	45	--	nC	

Notes:

- * 1. The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper.
- * 2. Pulse Test: Pulse width ≤ 300μs, Duty Cycle ≤ 2%.
- * 3. The power dissipation is limited by 175°C junction temperature.
- * 4. The data is theoretically the same as ID and IDM, in real applications, should be limited by total power dissipation.

Typical Feature Curve






Fig 7: Normalized Breakdown Voltage VS. Junction Temperature




Fig 8: Normalized on Resistance VS. Junction Temperature




Fig 9: Maximum Safe Operating Area




Fig 10: Body Diode Forward Characteristics




Fig.11: Maximum Effective Transient Thermal Impedance, Junction-to-Case

Test Circuits and Waveforms




Fig 12: Gate Charge Test Circuit and Waveforms




Fig 13: Resistive Switching Test Circuit and Waveforms





Fig 14: Unclamped Inductive Switching Test Circuit and Waveforms

Package outline drawing(TO-252 Unit: mm)



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	2.10		2.50	0.083		0.098
A2	0		0.10	0		0.004
B	0.66		0.86	0.026		0.034
B2	5.18		5.48	0.202		0.216
C	0.40		0.60	0.016		0.024
C2	0.44		0.58	0.017		0.023
D	5.90		6.30	0.232		0.248
D1	5.30REF			0.209REF		
E	6.40		6.80	0.252		0.268
E1	4.63			0.182		
G	4.47		4.67	0.176		0.184
H	9.50		10.70	0.374		0.421
L	1.09		1.21	0.043		0.048
L2	1.35		1.65	0.053		0.065
V1		7°			7°	
V2	0°		6°	0°		6°

Disclaimers:

Reasunos Semiconductor Technology Co.Ltd (Reasunos) reserves the right to make changes without notice in order to improve reliability,function or design and to discontinue any product or service without notice .Customers should obtain the latest relevant information before orders and should verify that such information in current and complete.All products are sold subject to Reasunos's terms and conditions supplied at the time of orderacknowledgement.

Reasunos Semiconductor Technology Co.Ltd warrants performance of its hardware products to the specifications at the time of sale.Testing,reliability and quality control are used to the extene Reasunos deems necessary to support this warrantee. Except where agreed upon by contr- actual agreement,testing of all parameters of each product is not necessarily performed.

Reasunos Semiconductor Technology Co.Ltd does not assume any liability arising from the use of any product or circuit designs described herein.Customers are responsible for their products and applications using Reasunos's components.To minimize risk,customers must provide adequate design and operating safeguards.

Reasunos Semiconductor Technology Co.Ltd does not warrant or convey any license either expressed or implied under its patent rights,nor the rights of others.Reproduction of inform- ation in Reasunos's data sheets or data books is permissible only if reproduction is without modification oralteration.Reproduction of this information with any alteration is an unfair and deceptive business practice. Reasunos Semiconductor Technology Co.Ltd is not responsi- ble or liable for such altered documentation.

Resale of Reasunos's products with statements different from or beyond the parameters stated by Reasunos Semiconductor Technology Co.Ltd for that product or service voids all exp- ress or implied warranties for the associated Reasunos's product or service and is unfair and deceptive business practice. Reasunos Semiconductor Technology Co.Ltd is not responsi- ble or liable for such statements.

Life Support Policy:

Reasunos Semiconductor Technology Co.Ltd's Products are not authorized for use as cri- tical components in life support devices or systems without the expressed written approval of Reasunos Semiconductor Technology Co.Ltd.

As used herein:

1. Life support devices or systems are devices or systems which: a.are intended for surgical implant into the human body, b.support or sustain life,c.whose failuer to when properly used in accordance with instructions for used provided in the laeling,can be reasonably expected to result in significant injury to the user.

2.A critical component is any component of a life support device or system whose failure to system whose failure to perform can be reasonably expected to cause the failure of the life support device or system,or to affect its safety or effectiveness.